



CS300 SERIES TRANSFORMERS



MIL-PRF-27

ELECTRICAL SPECIFICATIONS

- **Operating Temperature:** -55°C to +125°C
- **Storage Temperature:** -60°C to +130°C
- **Insulation Resistance:** 10K MOhms minimum
- **Different electrical values available upon request**
- **Dielectric Withstanding Voltage:** 500 V_{AC}

FEATURES


- **Compact**, low profile, ideal for automatic placement
- Built to meet **MIL-PRF-27** specifications
- **Low Thermal Expansion, Transfer Molded Package**
- **Terminations:** Tin-lead
- **Other termination finishes available upon request**
- **Welded Internal Connections**
- **Moisture, Shock and Immersion Resistant**
- **Resistance to Soldering Heat:** 265°C for 10 secs

I _{PK} max (Amps)	ET (V-μS)	Turns Ratio
5 to 10	20 to 144	1:50 to 1:100


MARKINGS: LASER OR INK
ALL DIMENSIONS: INCHES

THRU-HOLE PACKAGES
ALSO AVAILABLE


Package	A max.	B max.	C max.
T-2	.610	.610	.475
T-4	.610	.610	.475



PACKAGE T-2



PACKAGE T-4



Vanguard P/N	*I _{PK} max (Amps)	ET ref (V-μS)	DCR max (Ohms)	Inductance ref (mH)	Package	Turns Ratio
CS301	5	20	0.72	2.2	T-2	1:1:50:50
CS302	10	72	1.5	5.3	T-2	1:1:50:50
CS303	5	20	0.72	2.2	T-4	1:1:50:50
CS304	10	72	1.4	5.3	T-4	1:1:50:50
CS305	5	40	3.8	8.9	T-2	1:1:100:100
CS306	10	144	2.9	21.3	T-2	1:1:100:100
CS307	5	40	3.8	8.9	T-4	1:1:100:100
CS308	10	144	2.9	21.0	T-4	1:1:100:100

Inductance measured at 10 kHz, 0.1 V_{RMS}

* Signal generated is a 25% duty cycle pulse wave

CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types








TOP VIEW


BOTTOM VIEW

RECOMMENDED MOUNTING
PAD CIRCUIT SIDE



T-2 PACKAGE



T-4 PACKAGE



MAGNIFIED SIDE VIEW



CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

CS300 SERIES

