



HCI5H SERIES

HIGH CURRENT INDUCTOR



RoHS VERSION AVAILABLE

HI-RELIABILITY

Inductance Range	DCR max (Ohms)	Current Rating (A)
0.14 uH - 10 mH	0.008 - 57.2	6.0 - 0.08

ELECTRICAL SPECIFICATIONS

- **Operating Temperature:** -55°C to +130°C
- **Storage Temperature:** -60°C to +135°C
- **Temperature Rise:** < 30°C
- **Dielectric Withstanding Voltage:** 100 V_{RMS}
- **Different electrical values available upon request**


FEATURES

- **Compact**, low profile, ideal for automatic placement
- **Terminations:** Tin-lead, Lead Free (RoHS)
- **Welded Internal Connections**
- **Moisture, Shock and Immersion Resistant**
- **Magnetically Shielded**
- **Other termination finishes available upon request**
- **Multiple Configurations:** Series, parallel, transformer, dual inductor

APPLICATIONS



- Filter inductors
- Power supplies
- Ripple suppressors
- DC/DC converters
- Common mode chokes
- SEPIC converters
- Isolation transformers

ALL DIMENSIONS: INCHES




THRU-HOLE & GULL-WING PACKAGES ALSO AVAILABLE

MARKINGS: LASER ETCH OR INK





IN	MM
0.290	7.37
0.260	6.60
0.230	5.85
0.185	4.70
0.105	2.67
0.085	2.16
0.025	0.64
0.010	0.25



RECOMMENDED MOUNTING PAD CIRCUIT SIDE

TYPICAL USER CONNECTIONS

SCHEMATIC



CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types





DATA TABLE

Vanguard P/N	Series Inductance (uH)	Series DCR max (Ohms)	Series Rated Current (Adc)	Series Inc. Current ΔL 10% (Adc)	Series Inc. Current ΔL 20% (Adc)
HCI5H-R56M*-*	0.56	0.030	3.0	7.2	9.9
HCI5H-121M*-*	1.3	0.040	2.6	4.8	6.6
HCI5H-221M*-*	2.2	0.050	2.3	3.6	5.0
HCI5H-501M*-*	5.0	0.080	2.0	2.4	3.3
HCI5H-102M*-*	10.0	0.140	1.6	1.8	2.5
HCI5H-252M*-*	25.0	0.220	1.2	1.1	1.5
HCI5H-502M*-*	50.0	0.410	0.94	0.75	1.0
HCI5H-752M*-*	75.0	0.490	0.94	0.62	0.86
HCI5H-103K*-*	100.0	0.580	0.86	0.53	0.74
HCI5H-253K*-*	250.0	1.50	0.54	0.33	0.46
HCI5H-503K*-*	500.0	3.20	0.36	0.24	0.33
HCI5H-753K*-*	750.0	5.10	0.28	0.20	0.27
HCI5H-104K*-*	1.0 mH	7.60	0.23	0.17	0.23
HCI5H-204K*-*	2.0 mH	13.1	0.17	0.12	0.17
HCI5H-304K*-*	3.0 mH	20.1	0.14	0.10	0.14
HCI5H-504K*-*	5.0 mH	25.8	0.12	0.08	0.11
HCI5H-754K*-*	7.5 mH	40.9	0.10	0.06	0.09
HCI5H-105K*-*	10.0 mH	57.2	0.08	0.05	0.07

Vanguard P/N	Parallel Inductance (uH)	Parallel DCR max (Ohms)	Parallel Rated Current (Adc)	Parallel Inc. Current ΔL 10% (Adc)	Parallel Inc. Current ΔL 20% (Adc)
HCI5H-R56M*-*	0.140	0.008	6.0	14.3	19.9
HCI5H-121M*-*	0.315	0.010	5.2	9.5	13.2
HCI5H-221M*-*	0.560	0.013	4.7	7.2	9.9
HCI5H-501M*-*	1.25	0.020	4.0	4.8	6.6
HCI5H-102M*-*	2.50	0.035	3.2	3.6	5.0
HCI5H-252M*-*	6.25	0.055	2.5	2.2	3.1
HCI5H-502M*-*	12.50	0.103	1.9	1.5	2.1
HCI5H-752M*-*	18.75	0.123	1.9	1.2	1.7
HCI5H-103K*-*	25.00	0.145	1.7	1.1	1.5
HCI5H-253K*-*	62.50	0.368	1.1	0.67	0.92
HCI5H-503K*-*	125.0	0.800	0.72	0.48	0.66
HCI5H-753K*-*	187.5	1.30	0.55	0.39	0.54
HCI5H-104K*-*	250.0	1.90	0.45	0.34	0.47
HCI5H-204K*-*	500.0	3.30	0.34	0.24	0.33
HCI5H-304K*-*	800.0	5.00	0.28	0.19	0.27
HCI5H-504K*-*	1.250 mH	6.50	0.24	0.15	0.21
HCI5H-754K*-*	1.875 mH	10.2	0.19	0.12	0.17
HCI5H-105K*-*	2.500 mH	14.3	0.16	0.11	0.15

1/ Inductance measured at 10 kHz, 0.1 V_{RMS}

2/ DCR measured at room temperature

3/ Current Rating is based on a 30°C maximum temperature rise at an ambient temperature of 100°C

4/ Incremental current is the approximate value that will result in a percentage drop of inductance as indicated in the table

5/ Maximum Weight: TBD

6/ Units are series mode tested only, parallel mode values are reference only

CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

HCI5H SERIES





VE PART NUMBER
STRUCTURE KEY

INDUCTANCE
(uH) (mH)

R56 = .56 uH
103 = 100 uH
504 = 5 mH

EXAMPLE: HCl5H-R56MS-1-T

TOLERANCE
(%)

K	± 10
M	± 20

TERMINATION

S	SnPb
R	Pure Tin

RELIABILITY

1	COTS/EM
7	Other

PACKAGING
(Default Bulk)

B	Bulk
T	Tape and Reel

Tape and reel specs
Pcs. / reel maximum: (7") 200, (13") 800
Pitch between parts: 12 mm
Tape width: 16 mm

Parts that don't meet minimum reel requirements will be supplied on cut tape








Tape and Reel not available for Thru-Hole or Gull-Wing Packages

CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

HCl5H SERIES













CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

HCI5H SERIES









CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

HCl5H SERIES





CUSTOM DESIGNS & MODIFICATIONS:

Other electrical configurations and performance characteristics are available in various sizes and package types

HCl5H SERIES

